

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
25 September 2003 (25.09.2003)


PCT

(10) International Publication Number  
**WO 03/079638 A1**

- (51) International Patent Classification<sup>7</sup>: **H04L 29/06**
- (21) International Application Number: **PCT/US03/07178**
- (22) International Filing Date: **11 March 2003 (11.03.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:  
60/363,589 12 March 2002 (12.03.2002) US  
60/445,264 5 February 2003 (05.02.2003) US
- (71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS, N.V. [NL/NL];**  
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **EPSTEIN, Michael, A. [US/US];** 10 Dorset Road, Spring Valley, NY 10977 (US).
- (74) Agent: **HALAJIAN, Dicran; PHILIPS INTELLECTUAL PROPERTY & STANDARDS, 580 White Plains Road, Tarrytown, NY 10591 (US).**
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: USING TIMING SIGNALS TO DETERMINE PROXIMITY BETWEEN TWO NODES



(57) Abstract: A system and method facilitates a determination of proximity between nodes based on the communication time between the node. A source node communicates a query, or "ping", to a target node. The target node is configured to automatically send a response to the sender of such a query. The communication time is determined based on the time duration between the transmission of the query and receipt of the response at the source node. The communication time is compared to a threshold value to determine whether the target node is local or remote relative to the source node.

WO 03/079638 A1

**Declarations under Rule 4.17:**

- as to the identity of the inventor (Rule 4.17(i)) for all designations
- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European

patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations

**Published:**

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

## USING TIMING SIGNALS TO DETERMINE PROXIMITY BETWEEN TWO NODES

This invention relates to the field of communications security, and in particular, to a system and method that  
5 verifies the proximity of a node on a network.

Network security can often be enhanced by distinguishing between 'local' nodes and 'remote' nodes on the network. In like manner, different rights or restrictions may be imposed on the distribution of material to nodes, based on whether  
10 the node is local or remote. Local nodes, for example, are typically located within a particular physical environment, and it can be assumed that users within this physical environment are authorized to access the network and/or authorized to receive files from other local nodes. Remote  
15 nodes, on the other hand, are susceptible to unauthorized physical access. Additionally, unauthorized intruders on a network typically access the network remotely, via telephone or other communication channels. Because of the susceptibility of the network to unauthorized access via  
20 remote nodes, network security and/or copy protection can be enhanced by imposing stringent security measures and/or access restrictions on remote nodes, while not encumbering local nodes with these same restrictions.

It is an object of this invention to provide a system  
25 and method that facilitates a determination of whether a node on a network is local or remote. It is a further object of this invention to integrate this determination with a system or method that enforces security measures and access restrictions based on whether the node is local or remote.

30 These objects and others are achieved by a system and method that facilitates a determination of communication time between a source node and a target node. The proximity of the target node to the source node is determined from the

communication time. The source node communicates a query, or "ping", to the target node. The target node is configured to automatically send a response to the sender of such a query. The communication time is determined based on the time

5 duration between the transmission of the query and receipt of the response at the source node. The communication time is compared to a threshold value to determine whether the target node is local or remote relative to the source node.

FIG. 1 illustrates an example block diagram of a network of  
10 nodes.

FIG. 2 illustrates an example block diagram of a source and target node that effect a query-response protocol in accordance with this invention.

Throughout the drawings, the same reference numeral refers to  
15 the same element, or an element that performs substantially the same function.

FIG. 1 illustrates an example block diagram of a network  
150 of nodes 110. One of the nodes, NodeD 110, is illustrated as being distant from the other nodes 110. In accordance with  
20 this invention, each of the nodes 110 is configured to be able to determine the proximity of each other node 110. In a typical embodiment of this invention, the proximity determination is limited to a determination of whether the other node is "local" or "remote", although a more precise  
25 determination of distance may also be determined, as detailed below.

FIG. 2 illustrates an example block diagram of a source node 110S and target node 110T that effect a query-response protocol to determine the proximity of the target node 110T  
30 to the source node 110S in accordance with this invention. The source node 110S includes a processor 210 that initiates a query, and a communications device 220 that transmits the query to the target node 110T. The target node 110T receives

the query and returns a corresponding response, via its communications device 230. Conventional techniques, such as the TCP/IP network command "ping" operation, can be used to effect this query and response.

5        In a preferred embodiment, the query includes an identification of the source node in a form that facilitates a rapid response. For example, the query preferably includes the address of the target node and the address of the source node arranged in such a manner that the target node need only  
10       strip its address from the query to form the response. Generally, the response is generated at the processor 240 of the target node 110T, although in a preferred embodiment, the response to the query is generated automatically at the communications device 230 of the target node, to minimize the  
15       time required to process the query and generate the response, illustrated in FIG. 2 as the processing time,  $T_{\text{process}}$  270.

      The source node 110S is configured to measure the time consumed by the query-response process, and from this measure, to determine the proximity of the target node 110T.  
20       The query-response time includes the time to communicate the query and response, as well as the aforementioned processing time at the target node 110T. The processing time will vary based on the speed and configuration of the target node 110T. Within a local network, the processing time may exceed the  
25       actual communication time,  $T_{\text{communicate}}$  260, and thus the measure of the communication time is unreliable. However, if the target node 110T is remote from the source node 110S, the communication time will generally be substantially longer than the expected processing time, and thus the total time,  
30        $T_{\text{query-response}}$  280, can be expected to substantially correspond to the communication time. By comparing the query-response time to a nominal threshold value, typically not more than a few milliseconds, the proximity of the target node 110T to

the source node 110S can be determined. If the communication time is below the threshold, the target 110T is determined to be local; otherwise, it is determined to be remote.

Optionally, multiple threshold levels may be defined to  
5 distinguish different ranges of distances, such as whether a remote target node is located within the same country as the source node, and so on.

In a typical embodiment, the source 110S uses the remote/local proximity determination to control subsequent  
10 communications with the target 110T. For example, some files may be permitted to be transferred only to local nodes, all communications with a remote node may be required to be encrypted, and so on.

The foregoing merely illustrates the principles of the  
15 invention. It will thus be appreciated that those skilled in the art will be able to devise various arrangements which, although not explicitly described or shown herein, embody the principles of the invention and are thus within the spirit and scope of the following claims.

## CLAIMS:

1. A method of determining proximity of a target node to a source node, comprising:
  - communicating a query from the source node to the target node,
  - communicating a response from the target node to the source node,
  - receiving the response at the source node,
  - determining a measure of query-response time between communicating the query and receiving the response, and
  - determining the proximity of the target node based on the measure of query-response time.
2. The method of claim 1, wherein
  - determining the proximity includes comparing the query-response time to a threshold value that distinguishes between local and remote nodes.
3. The method of claim 2, further including
  - restricting communications with the target node based on the proximity.
4. The method of claim 1, further including
  - restricting communications with the target node based on the proximity.
5. The method of claim 1, wherein
  - communicating the query and response is effected via a TCP/IP ping network command.
6. A node on a network including:

a communication device that is configured to transmit a query to a target node and to receive a corresponding response from the target node,

the response from the target node including a measure of processing time required to generate the response at the target node, and

a processor that is configured to:

generate the query,

receive the response,

measure a query-response time between generating the query and receiving the response, and

determine a proximity of the target node relative to the node based on the query-response time.

7. The node of claim 6, wherein

the processor is configured to determine the proximity based on a comparison of the query-response time to a threshold value that distinguishes between local and remote nodes.

8. The node of claim 7, wherein

the processor is further configured to control subsequent communications with the target node based on the proximity.

9. The node of claim 6, wherein

the processor is further configured to control subsequent communications with the target node based on the proximity.

10. The node of claim 6, wherein

the processor generates the query using a TCP/IP ping network command.

1/1




FIG. 1




FIG. 2

# INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/US 03/07178

<b>A. CLASSIFICATION OF SUBJECT MATTER</b> IPC 7 H04L29/06		
According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) IPC 7 H04L		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EPO-Internal, WPI Data, PAJ, INSPEC, COMPENDEX, IBM-TDB		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	STEVENS ET AL: "TCP/IP ILLUSTRATED, Vol. 1. THE PROTOCOLS", TCP/IP ILLUSTRATED. VOL. 1: THE PROTOCOLS, PROFESSIONAL COMPUTING SERIES, READING, MA: ADDISON WESLEY, US, VOL. VOL. 1, PAGE(S) 85-96 XP002106390 ISBN: 0-201-63346-9 page 85 -page 87	1-10
Y	US 2002/016831 A1 (BARATZ ARIK ET AL) 7 February 2002 (2002-02-07) abstract paragraphs '0002!, '0004!, '0019!-'0026!, '0062!-'0065!, '0110!-'0112!, '0206!, '0210! --- -/--	1,2,5-7, 10
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C.		
<input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents : 'A' document defining the general state of the art which is not considered to be of particular relevance 'E' earlier document but published on or after the international filing date 'L' document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) 'O' document referring to an oral disclosure, use, exhibition or other means 'P' document published prior to the international filing date but later than the priority date claimed 'T' later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention 'X' document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone 'Y' document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. '&' document member of the same patent family		
Date of the actual completion of the international search 6 June 2003		Date of mailing of the international search report 13/06/2003
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer Lopez Monclus, I.

# INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/US 03/07178

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 6 308 273 B1 (SHAH BHARAT ET AL) 23 October 2001 (2001-10-23) abstract; figure 3 column 1, line 1-17, 55-63 column 5, line 12-50 ----	3, 4, 8, 9
P, X	US 2003/046022 A1 (SILVERMAN ROBERT M) 6 March 2003 (2003-03-06) abstract paragraphs '0002!', '0005!', '0008!', '0023!; claims 1-3 ----	1-10
P, X	US 2002/087666 A1 (HUFFMAN STEPHEN MARK ET AL) 4 July 2002 (2002-07-04) abstract paragraphs '0001!-'0003!', '0008!', '0034!', '0036! claim 1 ----	1, 5, 6, 10
P, X	US 6 505 240 B1 (BLUMENAU TREVOR I) 7 January 2003 (2003-01-07) abstract column 1, line 6-16 column 10, line 25-46 column 11, line 25-47 ----	1, 5, 6, 10
A	FRANCIS P ET AL: "An architecture for a global Internet host distance estimation service" INFOCOM '99. EIGHTEENTH ANNUAL JOINT CONFERENCE OF THE IEEE COMPUTER AND COMMUNICATIONS SOCIETIES. PROCEEDINGS. IEEE NEW YORK, NY, USA 21-25 MARCH 1999, PISCATAWAY, NJ, USA, IEEE, US, 21 March 1999 (1999-03-21), pages 210-217, XP010323734 ISBN: 0-7803-5417-6 page 210 -----	1, 5, 6, 10

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No.

PCT/US 03/07178

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 2002016831	A1	07-02-2002	NONE	
US 6308273	B1	23-10-2001	EP 1095493 A1 JP 2002518720 T WO 9965207 A1	02-05-2001 25-06-2002 16-12-1999
US 2003046022	A1	06-03-2003	US 2003046577 A1	06-03-2003
US 2002087666	A1	04-07-2002	WO 02063488 A1	15-08-2002
US 6505240	B1	07-01-2003	NONE	